

Ambu® WhiteSensor WS

ECG Electrode - Single use



Key Benefits

- Highly conductive solid gel
- Strong adhesion
- Comfortable foam backing

Ambu® WhiteSensor WS

The Ambu WhiteSensor WS features a highly conductive solid gel with strong adhesion to ensure a good signal quality during short-term ECG monitoring applications.

Thanks to the flexible foam backing material, the electrode ensures ease of use and comfort during application.



Solid gel



Foam backing

WhiteSensor

Specifications

Dimensions	
Electrode size (W x L in mm)	36 x 40
Skin contact size (W x L in mm)	36 x 40
Adhesive area (in mm ²)	857
Height excluding connector/wire (in mm)	1
Sensor	
Sensor material	Silver/silver chloride
Gel system	Solid
Sensor area (in mm ²)	79
Gel area/measuring area (in mm ²)	201
Electrical data (ANSI/AAMI)	
AC impedance - typical	150 Ω
DC offset voltage - typical	1.0 mV
Defibrillation overload recovery - typical	12 mV
Rate of change of polarization potential - typical	0.3 mV/s
Combined offset instability and internal noise	9 µV
Bias current tolerance (over 8 hours)	5 mV
Environment	
PVC-free electrode	Yes
Electrode not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	No
MR Conditional	No
Shelf life	
Opened pouches	1 month
Unopened pouches	30 months*

*from date of production

Materials

Electrode		Standard Packaging	
Bio-compatible	Yes	Quantity/pouch	3, 4, 5, 10, 30, 50
Sensor	Silver/silver chloride (Ag/AgCl)	Quantity/box	600/3600, 600/7200
Outer carrier	Polyethylene foam (PE)	Minimum sales	600/3600, 600/7200
Outer adhesive	Polyacrylate		
Connector (stud)	Stainless steel		
Liner	Siliconized polyester film		
Packaging		Options	
Outer	Polyester	Connectors	S
Middle	Aluminum	Precaution	
Inner	Poly film	Single use only	
Inner and outer carton	Corrugated box		

Available configurations

Reference number	Units/card	Units/pouch	Units/inner box	Units/outer box
WS-00-S/50	1	50	600	7200
WS-00-S/L5/50	5	50	600	7200
WS-00-S/3	3	3	600	3600
WS-00-S/4	4	4	600	3600
WS-00-S/5	5	5	600	3600
WS-00-S/10	5	10	600	3600
WS-00-S/30	1	30	600	7200

- Product
- WS-00-S
- Wire length
- Connector

Ambu A/S
 Baltorpbakken 13
 DK - 2750 Ballerup
 Denmark
 Tel. +45 7225 2000
 Fax +45 7225 2053
 www.ambu.com